

Features:

- Go Green All the veneers in RightPly® plywood come from plantation and sustainable wood sources. RightPly® plywood contains no tropical species.
- **Multi-purpose Panel** *RightPly*® plywood is ideal for a variety of interior applications, including flooring underlayment, paneling, millwork and woodworking projects*.
- Approved For Use Under These Flooring Products The 5 mm (nominal) thickness is approved under sheet vinyl, vinyl composite tile (VCT), luxury vinyl tile (LVT), luxury vinyl plank (LVP), carpet, engineered flooring, cork floors, and wood floors.
- NGBS Green Certified RightPly® plywood is certified for points toward ICC-700 National Green Building Standard™ (NGBS).
- Awarded Utility US Patent in April 2013 U.S. Patent No. 8,414,996
- Premium Grade and Appearance Every panel has a B grade or better rotary face veneer – free of repairs and defects.
- Strength & Stability 5-ply construction with machine-dried cores.
- **Easy to Use** Straight uniform grain for ease of cutting, scoring, finishing, and applying adhesives.
- Best Packaging in the Industry All crates of RightPly® plywood include two layers of packaging for complete product protection and damage-free arrival.
- Online Support The RightPly® plywood Warranty and Installation Instructions are available at www.RightPly.com.
- EPA TSCA Title VI Compliant

Specifications:

- Thicknesses from 2.7 mm up to 18 mm
- Sizes 4' x 8', 3' x 7' and other widely used plywood sizes
- 5.2 mm (nominal) x 4' x 8'
 18 lbs/sheet (approximate weight)
 100 pieces per crate
 26 crates per truckload
- 5.2 mm (nominal) x 4' x 4'
 9 lbs/sheet (approximate weight)
- Only the 5.2 mm (nominal) thickness is approved as an underlayment
- 2.7 mm x 4' x 8'
 11 lbs/sheet (approximate weight)
- EPA TSCA Title VI Compliant



Protective Packaging



PATRIOT TIMBER

the revolutionary source®

Post Office Box 19065 • Greensboro, North Carolina 27419 Telephone 336.299.7755 • Facsimile 336.299.4050

www.PatriotTimber.com

www.RightPly.com