Features:

- Go Green All the veneers in RevolutionPly® plywood come from plantation and sustainable wood sources. RevolutionPly® plywood contains no tropical species.
- Multi-purpose Panel RevolutionPly® plywood is ideal for a variety of interior applications, including flooring underlayment, paneling, millwork and woodworking projects*.
- Flooring Industry Approved 5.2 mm (nominal) thickness
 RevolutionPly® plywood has been tested and approved by major flooring
 manufacturers. RevolutionPly® plywood is the only Lauan plywood
 substitute that has been approved by flooring manufacturers for use as
 underlayment.
- Approved For Use Under These Flooring Products Sheet vinyl, vinyl composite tile (VCT), luxury vinyl tile (LVT), luxury vinyl plank (LVP), carpet, engineered flooring, cork floors, and wood floors.
- NGBS Green Certified RevolutionPly® plywood is certified for points toward ICC-700 National Green Building Standard™ (NGBS).
- Third Party Certified RevolutionPly® plywood has been given a low risk assessment for legal and environmental issues related to its wood sourcing.
- Awarded Utility US Patent in April 2013
 U.S. Patent No. 8,414,996
- Awarded Method US Patent in January 2016
 U.S. Patent No. 9,242,391
- Premium Grade and Appearance 100% uniform light color from sheet to sheet. Every panel has an A grade face veneer.
- Strength & Stability 5-ply construction with machine-dried cores.
- **Easy to Use** Straight uniform grain for ease of cutting, scoring, finishing, and applying adhesives.
- Best Packaging in the Industry All crates of RevolutionPly®
 Plywood include two layers of packaging for complete product protection and damage-free arrival.
- **Online Support** The *RevolutionPly*® plywood Warranties, Installation Instructions, and Video are all available at **www.RevolutionPly.com**.
- EPA TSCA Title VI Compliant

Specifications:

- Thicknesses from 2.7 mm up to 18 mm
- Sizes 4' x 8', 3' x 7' and other widely used plywood sizes
- 5.2 mm (nominal) x 4' x 8'
 100 pieces per crate
 26 crates per truckload
 17 lbs/sheet (approximate weight)
- Only the 5.2 mm (nominal) thickness is approved as an underlayment
- EPA TSCA Title VI Compliant

*Panels are designed for interior applications only



Protective Packaging



the revolutionary source®

Post Office Box 19065 • Greensboro, North Carolina 27419 Telephone 336.299.7755 • Facsimile 336.299.4050

www.PatriotTimber.com

www.RevolutionPly.com